

# 1409 // DRIVER

Leather gloves  
PPE risk category II



Protection against contact heat (100° C, 15 seconds)

Perfect fit

Particularly supple and resistant



## 1409 // DRIVER

**Material:** Cow grain leather, grey

**Coating:** -

**Size(s):** 8-12

**Packaging unit:** 60 pair(s)

**Certification:** EN 388, EN 407

NITRAS DRIVER, cow grain leather gloves, grey (colour code: 1200), with elastic at the back of the hand, wing thumb, large style, perfect fit, protection against contact heat (100° C, 15 seconds), premium quality, particularly supple and resistant, PPE risk category II



EN ISO 21420



| Size                 | 8                                                                                  | 9                                                                                  | 10                                                                                  | 11                                                                                   | 12                                                                                   |
|----------------------|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Colour coding system |  |  |  |  |  |

### Industries

-  Craft
-  Building / Construction
-  Automotive manufacturing
-  Commissioning / shipping
-  Landscape gardening
-  Waste management

### Advantages

- + Protection against contact heat (100° C, 15 seconds)
- + Perfect fit
- + Particularly supple and resistant



## Performance values

| EN ISO 21420:2020                                                                           | Test parameter                                 | Performance levels | Test result |
|---------------------------------------------------------------------------------------------|------------------------------------------------|--------------------|-------------|
|                                                                                             | Dexterity                                      | 1-5                | 5           |
| EN 388:2016 + A1:2018                                                                       | Test parameter                                 | Performance levels | Test result |
| <br>3122X  | Abrasion resistance                            | 1-4                | 3           |
|                                                                                             | Blade cut resistance (Coupe test)              | 1-5                | 1           |
|                                                                                             | Tear resistance                                | 1-4                | 2           |
|                                                                                             | Puncture resistance                            | 1-4                | 2           |
|                                                                                             | Blade cut resistance (TDM)                     | A-F                | X           |
| EN 407:2020                                                                                 | Test parameter                                 | Performance levels | Test result |
| <br>X1XXXX | Resistance to flammability                     | 1-4                | X           |
|                                                                                             | Contact heat resistance                        | 1-4                | 1           |
|                                                                                             | Convective heat resistance                     | 1-4                | X           |
|                                                                                             | Radiant heat resistance                        | 1-4                | X           |
|                                                                                             | Resistance to small splashes of molten metal   | 1-4                | X           |
|                                                                                             | Resistance to large quantities of molten metal | 1-4                | X           |

## Additional information

|                        | Material          | Colour |
|------------------------|-------------------|--------|
| Palm                   | Cow grain leather | grey   |
| Index finger and thumb | Cow grain leather | grey   |
| Back of the hand       | Cow grain leather | grey   |
| Fingertips             | Cow grain leather | grey   |
| Cuff / knitted wrist   | Cow grain leather | grey   |

## Logistics data

| Size | GTIN (SPU)    | GTIN (PU)     | Length (m) | Width (m) | Height (m) | Weight (kg) | Quantity PU / pallet |
|------|---------------|---------------|------------|-----------|------------|-------------|----------------------|
| 8    | 4059904098077 | 4059904098084 | 0,4 m      | 0,29 m    | 0,29 m     | 5,83 kg     | 45                   |
| 9    | 4059904098091 | 4059904098107 | 0,4 m      | 0,29 m    | 0,29 m     | 6,45 kg     | 45                   |
| 10   | 4059904098114 | 4059904098121 | 0,4 m      | 0,29 m    | 0,29 m     | 6,79 kg     | 45                   |
| 11   | 4059904098138 | 4059904098145 | 0,4 m      | 0,29 m    | 0,29 m     | 8,17 kg     | 45                   |
| 12   | 4059904098152 | 4059904098169 | 0,4 m      | 0,29 m    | 0,29 m     | 8,34 kg     | 45                   |

Customs tariff number: 42032910000

Country of origin: India