

# 3250 // CHEM PROTECT

Chemical protective gloves  
PPE risk category III



Particularly sensitive  
Very slip resistant  
Very good dry and wet grip



## 3250 // CHEM PROTECT



|                 |                    |
|-----------------|--------------------|
| Material:       | Latex, orange      |
| Coating:        | -                  |
| Size(s):        | 7-11               |
| Packaging unit: | 144 pair(s)        |
| Certification:  | EN 388, EN ISO 374 |

NITRAS CHEM PROTECT, chemical protective gloves, latex, orange (colour code: 4400), length 30 cm, flock lined, protection against micro-organisms and bacteria, for food contact, particularly sensitive, perfect for working with small parts, very slip resistant, very good tactile sensitivity, very good dry and wet grip, pairwise per polybag, PPE risk category III

EN 420

EN 388

ISO 374-1:2016/Type A

ISO 374-5:2016



2111X

AKLNOT



### Industries

-  Building / Construction
-  Cleaning / Facility management
-  Food industry
-  Landscape gardening
-  Waste management
-  Chemistry / laboratory

### Advantages

- + Particularly sensitive
- + Very slip resistant
- + Very good dry and wet grip



## Performance values

| EN 388:2016 + A1:2018                                                                       | Test parameter                    | Performance levels | Test result |
|---------------------------------------------------------------------------------------------|-----------------------------------|--------------------|-------------|
| <br>2111X  | Abrasion resistance               | 1-4                | 2           |
|                                                                                             | Blade cut resistance (Coupe test) | 1-5                | 1           |
|                                                                                             | Tear resistance                   | 1-4                | 1           |
|                                                                                             | Puncture resistance               | 1-4                | 1           |
|                                                                                             | Blade cut resistance (TDM)        | A-F                | X           |
| EN 420:2003 + A1:2009                                                                       | Test parameter                    | Performance levels | Test result |
|                                                                                             | Dexterity                         | 1-5                | 5           |
| EN ISO 374-1:2016                                                                           | Test parameter                    | Performance levels | Test result |
| <br>AKLNOT | A - Methanol                      | 1-6                | 2 (> 30)    |
|                                                                                             | K - Sodium hydroxide 40%          | 1-6                | 6 (> 480)   |
|                                                                                             | L - Sulphuric acid 96%            | 1-6                | 5 (> 240)   |
|                                                                                             | N - Acetic acid 99%               | 1-6                | 3 (> 60)    |
|                                                                                             | O - Ammonia water 25%             | 1-6                | 2 (> 30)    |
|                                                                                             | T - Formaldehyde 37%              | 1-6                | 6 (> 480)   |
| EN ISO 374-5:2016                                                                           | Test parameter                    | Performance levels | Test result |
|          | Penetration                       | -                  | Passed      |
|                                                                                             | Protection against viruses        | -                  | -           |

## Additional information

|                        | Material | Colour |
|------------------------|----------|--------|
| Palm                   | Latex    | orange |
| Index finger and thumb | Latex    | orange |
| Back of the hand       | Latex    | orange |
| Fingertips             | Latex    | orange |
| Cuff / knitted wrist   | Latex    | orange |

## Thickness (approx.)

|        |        |
|--------|--------|
| Finger | 0,7 mm |
| Palm   | 0,7 mm |

## Logistics data

| Size | GTIN (SPU)    | GTIN (PU)     | Length (m) | Width (m) | Height (m) | Weight (kg) | Quantity PU / pallet |
|------|---------------|---------------|------------|-----------|------------|-------------|----------------------|
| 7    | 4059904100008 | 4059904100015 | 0,48 m     | 0,31 m    | 0,38 m     | 14,92 kg    | 22                   |
| 8    | 4059904100022 | 4059904100039 | 0,47 m     | 0,31 m    | 0,38 m     | 15,67 kg    | 22                   |
| 9    | 4059904100046 | 4059904100053 | 0,48 m     | 0,31 m    | 0,38 m     | 16,89 kg    | 22                   |
| 10   | 4059904100060 | 4059904100077 | 0,47 m     | 0,41 m    | 0,3 m      | 18,64 kg    | 22                   |
| 11   | 4059904100084 | 4059904100091 | 0,47 m     | 0,41 m    | 0,3 m      | 20,15 kg    | 22                   |

Customs tariff number: 40151900000

Country of origin: Sri Lanka