

3455 // GREEN BARRIER GRIP

Chemical protective gloves
PPE risk category III



Very good dry and oil grip
Very high abrasion resistance
Very robust and resistant



3455 // GREEN BARRIER GRIP



Material:	Cotton interlock, natural colour
Coating:	Nitrile, green Nitrile, sanded, black
Size(s):	7-12
Packaging unit:	72 pair(s)
Certification:	EN 388, EN ISO 374

NITRAS GREEN BARRIER GRIP, chemical protective gloves, cotton interlock, natural colour, double layer coating, lower coating: nitrile, green, fully coated, upper coating: sanded nitrile, black (colour code: 2510), partly coated on palm and fingertips, length 32 cm, very good dry and oil grip, protection against micro-organisms, bacteria and viruses, for food contact, particularly sensitive, perfect for working with small parts, very good tactile sensitivity, very good dry and oil grip, very high abrasion resistance, very robust and resistant, pairwise per polybag, PPE risk category III



EN ISO 21420



Industries





-  Building / Construction
-  Cleaning / Facility management
-  Food industry
-  Landscape gardening
-  Waste management
-  Chemistry / laboratory

Advantages

- + Very good dry and oil grip
- + Very high abrasion resistance
- + Very robust and resistant



Performance values

EN 388:2016 + A1:2018	Test parameter	Performance levels	Test result
 4121X	Abrasion resistance	1-4	4
	Blade cut resistance (Coupe test)	1-5	1
	Tear resistance	1-4	2
	Puncture resistance	1-4	1
	Blade cut resistance (TDM)	A-F	X
EN 407:2020	Test parameter	Performance levels	Test result
 X1XXXX	Resistance to flammability	1-4	X
	Contact heat resistance	1-4	1
	Convective heat resistance	1-4	X
	Radiant heat resistance	1-4	X
	Resistance to small splashes of molten metal	1-4	X
	Resistance to large quantities of molten metal	1-4	X
EN ISO 374-1:2016 + A1:2018	Test parameter	Performance levels	Test result
 AJKMNO	A - Methanol	1-6	3 (> 60)
	J - n-Heptane	1-6	5 (> 240)
	K - Sodium hydroxide 40%	1-6	6 (> 480)
	L - Sulphuric acid 96%	1-6	2 (> 30)
	M - Nitric acid 65%	1-6	2 (> 30)
	N - Acetic acid 99%	1-6	2 (> 30)
	O - Ammonia water 25%	1-6	4 (> 120)
	P - Hydrogen peroxide 30%	1-6	5 (> 240)
	T - Formaldehyde 37%	1-6	6 (> 480)
EN ISO 374-5:2016	Test parameter	Performance levels	Test result
 VIRUS	Penetration	-	Passed
	Protection against viruses	-	Passed
EN ISO 21420:2020	Test parameter	Performance levels	Test result
	Dexterity	1-5	5

Additional information

	Material	Colour
Palm	Nitrile, sanded, on nitrile and cotton interlock	black
Index finger and thumb	Nitrile, sanded, on nitrile and cotton interlock	black
Back of the hand	Nitrile on cotton interlock	green
Fingertips	Nitrile, sanded, on nitrile and cotton interlock	black
Cuff / knitted wrist	Nitrile on cotton interlock	green

Thickness

Finger	1,3 mm
Palm	1,3 mm
Cuff	1,3 mm

Logistics data

Size	GTIN (SPU)	GTIN (PU)	Length (m)	Width (m)	Height (m)	Weight (kg)	Quantity PU / pallet
7	4059904156357	4059904156364	0,46 m	0,37 m	0,24 m	8,2 kg	30
8	4059904156272	4059904156319	0,46 m	0,37 m	0,24 m	8,3 kg	24
9	4059904156289	4059904156326	0,46 m	0,37 m	0,24 m	8,65 kg	24
10	4059904156296	4059904156333	0,46 m	0,37 m	0,24 m	9,05 kg	24
11	4059904156302	4059904156340	0,46 m	0,37 m	0,24 m	9,25 kg	24
12	4059904235656	4059904235663	0,46 m	0,37 m	0,3 m	11,25 kg	30

Customs tariff number: 61161020910

Country of origin: China