

# 6735 // CUT C

PPE risk category II



very high abrasion resistance

very good dry and oil grip

Protection against contact heat (100° C, 15 seconds)

13  
GAUGE

NI



## 6735 // CUT C

|                        |                          |
|------------------------|--------------------------|
| <b>Material:</b>       | TAEKI special yarn, blue |
| <b>Coating:</b>        | Nitrile foam, black      |
| <b>Size(s):</b>        | 6-11                     |
| <b>Packaging unit:</b> | 100 pair(s)              |
| <b>Certification:</b>  | EN 388, EN 407           |

NITRAS CUT C, cut protection gloves, TAEKI special yarn (HPPE / polyester / glass fibre / elastane), blue, nitrile foam coating, black (colour code: 2210), partly coated on palm and fingertips, knitted wrist, high cut resistance, protection against contact heat (100° C, 15 seconds), highest wearing comfort, highest dexterity, very high abrasion resistance, very good dry and oil grip, PPE risk category II



EN ISO 21420

13  
GAUGE



| Size                 | 6                                                                                   | 7                                                                                   | 8                                                                                   | 9                                                                                     | 10                                                                                    | 11                                                                                    |
|----------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Colour coding system |  |  |  |  |  |  |

### Industries

-  Craft
-  Building / Construction
-  Automotive manufacturing
-  Commissioning / shipping
-  Wood processing

### Advantages

- + very high abrasion resistance
- + very good dry and oil grip
- + Protection against contact heat (100° C, 15 seconds)



# Performance values

| EN 388:2016 + A1:2018                                                                       | Test parameter                                 | Performance levels | Test result |
|---------------------------------------------------------------------------------------------|------------------------------------------------|--------------------|-------------|
| <br>4X43C  | Abrasion resistance                            | 1-4                | 4           |
|                                                                                             | Blade cut resistance (Coupe test)              | 1-5                | X           |
|                                                                                             | Tear resistance                                | 1-4                | 4           |
|                                                                                             | Puncture resistance                            | 1-4                | 3           |
|                                                                                             | Blade cut resistance (TDM)                     | A-F                | C           |
| EN 407:2020                                                                                 | Test parameter                                 | Performance levels | Test result |
| <br>X1XXXX | Resistance to flammability                     | 1-4                | X           |
|                                                                                             | Contact heat resistance                        | 1-4                | 1           |
|                                                                                             | Convective heat resistance                     | 1-4                | X           |
|                                                                                             | Radiant heat resistance                        | 1-4                | X           |
|                                                                                             | Resistance to small splashes of molten metal   | 1-4                | X           |
|                                                                                             | Resistance to large quantities of molten metal | 1-4                | X           |
| EN ISO 21420:2020                                                                           | Test parameter                                 | Performance levels | Test result |
|                                                                                             | Dexterity                                      | 1-5                | 5           |

## Additional information

|                        | Material                           | Colour |
|------------------------|------------------------------------|--------|
| Palm                   | Nitrile foam on TAEKI special yarn | black  |
| Index finger and thumb | Nitrile foam on TAEKI special yarn | black  |
| Back of the hand       | TAEKI special yarn                 | blue   |
| Fingertips             | Nitrile foam on TAEKI special yarn | black  |
| Cuff / knitted wrist   | TAEKI special yarn                 | blue   |

## Logistics data

| Size | GTIN (SPU)    | GTIN (PU)     | Length (m) | Width (m) | Height (m) | Weight (kg) | Quantity PU /<br>pallet |
|------|---------------|---------------|------------|-----------|------------|-------------|-------------------------|
| 6    | 4059904033153 | 4059904001572 | 0,68 m     | 0,32 m    | 0,29 m     | 8,11 kg     | 25                      |
| 7    | 4059904033160 | 4059904001589 | 0,68 m     | 0,3 m     | 0,32 m     | 8,28 kg     | 20                      |
| 8    | 4059904033177 | 4059904001596 | 0,68 m     | 0,31 m    | 0,33 m     | 10,12 kg    | 20                      |
| 9    | 4059904033184 | 4059904001602 | 0,68 m     | 0,3 m     | 0,33 m     | 11,26 kg    | 20                      |
| 10   | 4059904033191 | 4059904001619 | 0,68 m     | 0,33 m    | 0,29 m     | 11,4 kg     | 20                      |
| 11   | 4059904033207 | 4059904001626 | 0,67 m     | 0,31 m    | 0,32 m     | 10,89 kg    | 20                      |

Customs tariff number: 61161020910

Country of origin: China