

6845 // ESD 3D CUT F

Cut protection gloves
PPE risk category II



Perfect and innovative fit thanks 3D FIT
Antistatic (dissipative)
Highest cut resistance (performance level F)

13
GAUGE



6845 // ESD 3D CUT F



| | |
|------------------------|--------------------------------|
| Material: | Special yarn, black |
| Coating: | Nitrile micro foam, black |
| Size(s): | 6-12 |
| Packaging unit: | 100 pair(s) |
| Certification: | EN 388, OEKO-TEX STANDARD 100® |

NITRAS ESD 3D CUT F, cut protection gloves, special yarn (HPPE / steel / basalt / polyester / elastane / carbon), black, integrated carbon fibre, nitrile micro foam coating, black (colour code: 1000), partly coated on palm and fingertips, high mechanical resistance, knitted wrist, highest cut resistance (performance level F), perfect dexterity, perfect and innovative fit thanks 3D FIT, unique comfort and protection for the user, reinforced thumb crotch, touchscreen capable, washable, premium quality, antistatic (dissipative), skin compatibility tested (dermatest®), for food contact, OEKO-TEX STANDARD 100®, ANSI A6 CUT, very slip resistant, perfect grip, very high abrasion resistance, very good dry and oil grip, PPE risk category II



EN ISO 21420

13 GAUGE



| | | | | | | | |
|----------------------|---|---|---|---|----|----|----|
| Size | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
| Colour coding system | | | | | | | |

Industries



- Craft
- Building / Construction
- Automotive manufacturing
- Commissioning / shipping
- Wood processing

Advantages

- + Perfect and innovative fit thanks 3D FIT
- + Antistatic (dissipative)
- + Highest cut resistance (performance level F)




Performance values

| EN 16350:2014 | Test parameter | Performance levels | Test result |
|--|-----------------------------------|--------------------|------------------------|
|  | Palm (Ω) | - | 2,16 x 10 ⁶ |
| | Back of the hand (Ω) | - | 7,18 x 10 ⁶ |
| | Cuff (Ω) | - | 1,10 x 10 ⁶ |
| EN 388:2016 + A1:2018 | Test parameter | Performance levels | Test result |
|  4X42F | Abrasion resistance | 1-4 | 4 |
| | Blade cut resistance (Coupe test) | 1-5 | X |
| | Tear resistance | 1-4 | 4 |
| | Puncture resistance | 1-4 | 2 |
| | Blade cut resistance (TDM) | A-F | F |
| EN ISO 21420:2020 | Test parameter | Performance levels | Test result |
| | Dexterity | 1-5 | 5 |

Additional information

| | Material | Colour |
|------------------------|------------------------------------|--------|
| Palm | Nitrile micro foam on special yarn | black |
| Index finger and thumb | Nitrile micro foam on special yarn | black |
| Back of the hand | Special yarn | black |
| Fingertips | Nitrile micro foam on special yarn | black |
| Cuff / knitted wrist | Special yarn | black |



Washing cycles (max.) 5

Logistics data

| Size | GTIN (SPU) | GTIN (PU) | Length (m) | Width (m) | Height (m) | Weight (kg) | Quantity PU / pallet |
|------|---------------|---------------|------------|-----------|------------|-------------|----------------------|
| 6 | 4059904206731 | 4059904206809 | 0,56 m | 0,3 m | 0,28 m | 4,59 kg | 30 |
| 7 | 4059904206748 | 4059904206816 | 0,56 m | 0,3 m | 0,28 m | 4,99 kg | 30 |
| 8 | 4059904206755 | 4059904206823 | 0,56 m | 0,3 m | 0,28 m | 5,39 kg | 30 |
| 9 | 4059904206762 | 4059904206830 | 0,56 m | 0,3 m | 0,28 m | 5,79 kg | 30 |
| 10 | 4059904206779 | 4059904206847 | 0,56 m | 0,3 m | 0,28 m | 6,29 kg | 30 |
| 11 | 4059904206786 | 4059904206854 | 0,56 m | 0,3 m | 0,28 m | 6,79 kg | 30 |
| 12 | 4059904206793 | 4059904206861 | 0,56 m | 0,3 m | 0,28 m | 7,29 kg | 30 |

Customs tariff number: 61161020910

Country of origin: China