


8700ESD3D



Material:	Special stretch fabric, grey
Coating:	Nitrile foam coating, black
Size(s):	5-12
Packaging unit:	144 pair(s)
Certification:	EN 388, EN 407, OEKO-TEX STANDARD 100®

NITRAS assembly gloves, special stretch fabric (polyamide / elastane / carbon), grey, integrated carbon fibre, nitrile foam coating, black (colour code: 1210), partly coated on palm and fingertips, dark colours, long life, high mechanical resistance, very breathable, knitted wrist, perfect dexterity, perfect and innovative fit thanks 3D FIT, unique comfort and protection for the user, touchscreen capable, paint compatibility tested, washable, protection against contact heat (100°C, 15 seconds), premium quality, antistatic (dissipative), skin compatibility tested (dermatest®), OEKO-TEX STANDARD 100®, particularly sensitive, perfect for working with small parts, very slip resistant, perfect grip, high abrasion resistance (up to 15,000 abrasion cycles), PPE risk category II



Size	5	6	7	8	9	10	11	12
Colour coding system								

Industries




- Craft
- Building / Construction
- Automotive manufacturing
- Commissioning / shipping
- Landscape gardening

Advantages

- + Perfect grip
- + Skin compatibility tested (dermatest®)
- + High abrasion resistance (up to 15,000 abrasion cycles)




Performance values

EN 16350:2014	Test parameter	Performance levels	Test result
	Palm (resistance in Ω)	-	$7,35 \times 10^5$
	Back of the hand (resistance in Ω)	-	$4,96 \times 10^5$
	Cuff (resistance in Ω)	-	$1,62 \times 10^6$
EN 388:2016 + A1:2018	Test parameter	Performance levels	Test result
 4131X	Abrasion resistance	1-4	4
	Blade cut resistance (Coupe test)	1-5	1
	Tear resistance	1-4	3
	Puncture resistance	1-4	1
	Blade cut resistance (TDM)	A-F	X
EN 407:2020	Test parameter	Performance levels	Test result
 X1XXXX	Resistance to flammability	1-4	X
	Contact heat resistance	1-4	1
	Convective heat resistance	1-4	X
	Radiant heat resistance	1-4	X
	Resistance to small splashes of molten metal	1-4	X
	Resistance to large quantities of molten metal	1-4	X
EN ISO 21420:2020	Test parameter	Performance levels	Test result
	Dexterity	1-5	5

Additional information

	Material	Colour
Palm	Special coating on special stretch fabric	black
Index finger and thumb	Special coating on special stretch fabric	black
Back of the hand	Special stretch fabric	grey
Fingertips	Special coating on special stretch fabric	black
Cuff / knitted wrist	Special stretch fabric	grey



Washing cycles (max.) 5

Logistics data

Size	GTIN (SPU)	GTIN (PU)	Length (m)	Width (m)	Height (m)	Weight (kg)	Quantity PU / pallet
5	4059904195219	4059904195295	0,4 m	0,27 m	0,37 m	5,2 kg	36
6	4059904195226	4059904195301	0,4 m	0,27 m	0,37 m	5,39 kg	36
7	4059904195233	4059904195318	0,4 m	0,27 m	0,37 m	5,48 kg	36
8	4059904195240	4059904195325	0,4 m	0,27 m	0,37 m	6,31 kg	36
9	4059904195257	4059904195332	0,4 m	0,27 m	0,37 m	6,84 kg	36
10	4059904195264	4059904195349	0,41 m	0,27 m	0,37 m	7,06 kg	36
11	4059904195271	4059904195356	0,41 m	0,33 m	0,37 m	7,67 kg	36
12	4059904195288	4059904195363	0,41 m	0,33 m	0,37 m	8,2 kg	36

Customs tariff number: 61161020910

Country of origin: China