

8700 // SKIN FLEX 3D

Assembly gloves
PPE risk category II



High abrasion resistance (up to 10,000 abrasion cycles)
Protection against contact heat (100° C, 15 seconds)
Perfect and innovative fit thanks 3D FIT



8700 // SKIN FLEX 3D



| | |
|------------------------|--|
| Material: | Nylon, grey |
| Coating: | Nitrile foam, black |
| Size(s): | 6-11 |
| Packaging unit: | 144 pair(s) |
| Certification: | EN 388, EN 407, OEKO-TEX STANDARD 100® |

NITRAS SKIN FLEX 3D, assembly gloves, grey, nitrile foam coating, black (colour code: 1210), partly coated on palm and fingertips, knitted wrist, perfect and innovative fit thanks 3D FIT, unique comfort and protection for the user, perfect dexterity, protection against contact heat (100° C, 15 seconds), premium quality, touchscreen capable, OEKO-TEX STANDARD 100®, particularly sensitive, perfect for working with small parts, very slip resistant, perfect grip, high abrasion resistance (up to 10,000 abrasion cycles), PPE risk category II








EN ISO 21420

15 GAUGE



| | | | | | | |
|----------------------|---|---|---|---|---|---|
| Size | 6 | 7 | 8 | 9 | 10 | 11 |
| Colour coding system |  |  |  |  |  |  |

Industries



-  Craft
-  Building / Construction
-  Automotive manufacturing
-  Commissioning / shipping
-  Landscape gardening

Advantages

- + High abrasion resistance (up to 10,000 abrasion cycles)
- + Protection against contact heat (100° C, 15 seconds)
- + Perfect and innovative fit thanks 3D FIT



Performance values

| EN 388:2016 + A1:2018 | Test parameter | Performance levels | Test result |
|---|--|--------------------|-------------|
|  4131X | Abrasion resistance | 1-4 | 4 |
| | Blade cut resistance (Coupe test) | 1-5 | 1 |
| | Tear resistance | 1-4 | 3 |
| | Puncture resistance | 1-4 | 1 |
| | Blade cut resistance (TDM) | A-F | X |
| EN 407:2020 | Test parameter | Performance levels | Test result |
|  X1XXXX | Resistance to flammability | 1-4 | X |
| | Contact heat resistance | 1-4 | 1 |
| | Convective heat resistance | 1-4 | X |
| | Radiant heat resistance | 1-4 | X |
| | Resistance to small splashes of molten metal | 1-4 | X |
| | Resistance to large quantities of molten metal | 1-4 | X |
| EN ISO 21420:2020 | Test parameter | Performance levels | Test result |
| | Dexterity | 1-5 | 5 |

Additional information

| | Material | Colour |
|------------------------|-----------------------|--------|
| Palm | Nitrile foam on nylon | black |
| Index finger and thumb | Nitrile foam on nylon | black |
| Back of the hand | Nylon | grey |
| Fingertips | Nitrile foam on nylon | black |
| Cuff / knitted wrist | Nylon | grey |

Logistics data

| Size | GTIN (SPU) | GTIN (PU) | Length (m) | Width (m) | Height (m) | Weight (kg) | Quantity PU / pallet |
|------|---------------|---------------|------------|-----------|------------|-------------|----------------------|
| 6 | 4059904091566 | 4059904091573 | 0,4 m | 0,27 m | 0,37 m | 5,39 kg | 32 |
| 7 | 4059904091467 | 4059904091474 | 0,4 m | 0,36 m | 0,26 m | 5,48 kg | 32 |
| 8 | 4059904091481 | 4059904091498 | 0,4 m | 0,37 m | 0,26 m | 6,31 kg | 32 |
| 9 | 4059904091504 | 4059904091511 | 0,4 m | 0,37 m | 0,27 m | 6,84 kg | 32 |
| 10 | 4059904091528 | 4059904091535 | 0,41 m | 0,37 m | 0,27 m | 7,06 kg | 32 |
| 11 | 4059904091542 | 4059904091559 | 0,41 m | 0,33 m | 0,36 m | 7,67 kg | 32 |
| 12 | 4059904187832 | 4059904187849 | 0,41 m | 0,37 m | 0,36 m | 8,27 kg | 32 |

Customs tariff number: 61161020910

Country of origin: China