

# 8810 // FLEXIBLE FIT K

Assembly gloves

PPE risk category II



Perfect grip

Very high abrasion resistance

Very good dry and oil grip

15  
GAUGE

QUALITY  
PREMIUM

STANDARD  
100  
CERTIFIED  
BY  
ISO 9001

KVORENS  
THE QUALITY OF YOUR PROTECTION

NI

## 8810 // FLEXIBLE FIT K



|                        |                                        |
|------------------------|----------------------------------------|
| <b>Material:</b>       | KYORENE® special yarn, grey            |
| <b>Coating:</b>        | Nitrile foam, black                    |
| <b>Size(s):</b>        | 6-11                                   |
| <b>Packaging unit:</b> | 72 pair(s)                             |
| <b>Certification:</b>  | EN 388, EN 407, OEKO-TEX STANDARD 100® |

NITRAS FLEXIBLE FIT K, assembly gloves, KYORENE®-Special yarn, grey, nitrile foam coating, black (colour code: 1210), partly coated on palm and fingertips, knitted wrist, protection against contact heat (100° C, 15 seconds), perfect wearing comfort, perfect dexterity, premium-quality, OEKO-TEX STANDARD 100®, very slip resistant, perfect grip, very high abrasion resistance, very good dry and oil grip, PPE risk category II



EN ISO 21420



| Size                 | 6                                                                                   | 7                                                                                   | 8                                                                                   | 9                                                                                     | 10                                                                                    | 11                                                                                    |
|----------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Colour coding system |  |  |  |  |  |  |

### Industries

-  Craft
-  Building / Construction
-  Automotive manufacturing
-  Commissioning / shipping
-  Landscape gardening

### Advantages

- + Perfect grip
- + Very high abrasion resistance
- + Very good dry and oil grip



## Performance values

| EN 388:2016 + A1:2018                                                                       | Test parameter                                 | Performance levels | Test result |
|---------------------------------------------------------------------------------------------|------------------------------------------------|--------------------|-------------|
| <br>4121A  | Abrasion resistance                            | 1-4                | 4           |
|                                                                                             | Blade cut resistance (Coupe test)              | 1-5                | 1           |
|                                                                                             | Tear resistance                                | 1-4                | 2           |
|                                                                                             | Puncture resistance                            | 1-4                | 1           |
|                                                                                             | Blade cut resistance (TDM)                     | A-F                | A           |
| EN 407:2020                                                                                 | Test parameter                                 | Performance levels | Test result |
| <br>X1XXXX | Resistance to flammability                     | 1-4                | X           |
|                                                                                             | Contact heat resistance                        | 1-4                | 1           |
|                                                                                             | Convective heat resistance                     | 1-4                | X           |
|                                                                                             | Radiant heat resistance                        | 1-4                | X           |
|                                                                                             | Resistance to small splashes of molten metal   | 1-4                | X           |
|                                                                                             | Resistance to large quantities of molten metal | 1-4                | X           |
| EN ISO 21420:2020                                                                           | Test parameter                                 | Performance levels | Test result |
|                                                                                             | Dexterity                                      | 1-5                | 5           |

## Additional information

|                        | Material                              | Colour |
|------------------------|---------------------------------------|--------|
| Palm                   | Nitrile foam on KYORENE® special yarn | black  |
| Index finger and thumb | Nitrile foam on KYORENE® special yarn | black  |
| Back of the hand       | KYORENE® special yarn,                | grey   |
| Fingertips             | Nitrile foam on KYORENE® special yarn | black  |
| Cuff / knitted wrist   | KYORENE® special yarn,                | grey   |

## Logistics data

| Size | GTIN (SPU)    | GTIN (PU)     | Length (m) | Width (m) | Height (m) | Weight (kg) | Quantity PU / pallet |
|------|---------------|---------------|------------|-----------|------------|-------------|----------------------|
| 6    | 4059904098336 | 4059904098398 | 0,38 m     | 0,32 m    | 0,31 m     | 4,14 kg     | 60                   |
| 7    | 4059904098343 | 4059904098404 | 0,39 m     | 0,31 m    | 0,31 m     | 4,07 kg     | 60                   |
| 8    | 4059904098350 | 4059904098411 | 0,34 m     | 0,38 m    | 0,31 m     | 4,19 kg     | 60                   |
| 9    | 4059904098367 | 4059904098428 | 0,32 m     | 0,38 m    | 0,31 m     | 4,54 kg     | 60                   |
| 10   | 4059904098374 | 4059904098435 | 0,36 m     | 0,31 m    | 0,31 m     | 4,89 kg     | 60                   |
| 11   | 4059904098381 | 4059904098442 | 0,36 m     | 0,31 m    | 0,31 m     | 5,08 kg     | 32                   |

Customs tariff number: 61161020910

Country of origin: China