

# 8920 // DEXTER ULTIMATE CUT D

Mechanic's gloves

PPE risk category II



Protection against impact

Touchscreen capable

Perfect for working with small parts



GL



## 8920 // DEXTER ULTIMATE CUT D

|                 |                                      |
|-----------------|--------------------------------------|
| Material:       | Nappa leather, grey   Textile, black |
| Coating:        | -                                    |
| Size(s):        | 8-12                                 |
| Packaging unit: | 60 pair(s)                           |
| Certification:  | EN 388, EN 407                       |

NITRAS DEXTER ULTIMATE CUT D, mechanic's gloves, very sleek and resistant nappa leather, grey, premium textile back black (colour code: 1012), palm lined with special yarn, TPR knuckle protection, palm with cushioning gel pads, high cut resistance, protection against contact heat (100°C, 15 seconds), protection against impact, breathable, perfect sense of touch, excellent fitting due to hook and loop fastener at wrist, touchscreen capable, premium quality, particularly sensitive, perfect for working with small parts, very good tactile sensitivity, particularly supple and resistant, PPE risk category II



EN ISO 21420



### Industries

-  Craft
-  Building / Construction
-  Automotive manufacturing
-  Commissioning / shipping
-  Landscape gardening
-  Waste management

### Advantages

- + Protection against impact
- + Touchscreen capable
- + Perfect for working with small parts



## Performance values

| EN 388:2016 + A1:2018                                                                       | Test parameter                                 | Performance levels | Test result |
|---------------------------------------------------------------------------------------------|------------------------------------------------|--------------------|-------------|
| <br>3X43DP | Abrasion resistance                            | 1-4                | 3           |
|                                                                                             | Blade cut resistance (Coupe test)              | 1-5                | X           |
|                                                                                             | Tear resistance                                | 1-4                | 4           |
|                                                                                             | Puncture resistance                            | 1-4                | 3           |
|                                                                                             | Blade cut resistance (TDM)                     | A-F                | D           |
|                                                                                             | Protection against impact                      | P                  | P           |
| EN 407:2020                                                                                 | Test parameter                                 | Performance levels | Test result |
| <br>X1XXXX | Resistance to flammability                     | 1-4                | X           |
|                                                                                             | Contact heat resistance                        | 1-4                | 1           |
|                                                                                             | Convective heat resistance                     | 1-4                | X           |
|                                                                                             | Radiant heat resistance                        | 1-4                | X           |
|                                                                                             | Resistance to small splashes of molten metal   | 1-4                | X           |
|                                                                                             | Resistance to large quantities of molten metal | 1-4                | X           |
| EN ISO 21420:2020 + A1:2024                                                                 | Test parameter                                 | Performance levels | Test result |
|                                                                                             | Dexterity                                      | 1-5                | 5           |

## Additional information

|                        | Material                  | Colour       |
|------------------------|---------------------------|--------------|
| Palm                   | Nappa leather             | grey         |
| Index finger and thumb | Nappa leather and textile | grey / black |
| Back of the hand       | Textile with TPR          | black        |
| Fingertips             | Nappa leather and textile | grey / black |
| Cuff / knitted wrist   | Textile                   | black        |

## Logistics data

| Size | GTIN (SPU)    | GTIN (PU)     | Length (m) | Width (m) | Height (m) | Weight (kg) | Quantity PU /<br>pallet |
|------|---------------|---------------|------------|-----------|------------|-------------|-------------------------|
| 8    | 4059904207530 | 4059904207585 | 0,59 m     | 0,28 m    | 0,19 m     | 5,41 kg     |                         |
| 9    | 4059904207547 | 4059904207592 | 0,59 m     | 0,28 m    | 0,19 m     | 5,7 kg      |                         |
| 10   | 4059904207554 | 4059904207608 | 0,59 m     | 0,28 m    | 0,19 m     | 6 kg        |                         |
| 11   | 4059904207561 | 4059904207615 | 0,6 m      | 0,3 m     | 0,2 m      | 6,3 kg      |                         |
| 12   | 4059904207578 | 4059904207622 | 0,43 m     | 0,43 m    | 0,41 m     | 20 kg       |                         |

Customs tariff number: 42032910000

Country of origin: India